


Cometa[®]
costruzioni meccaniche



NOVITÀ
CROCHET CO.ME.TA.
CON SALVA AGO


VBO XXS H270 EVO
TRIPLICE TRASPORTO



VBO XXS H270 EVO TRIPLICE TRASPORTO



Macchina a braccio oscillante con crochet COMETA con salva ago, triplice trasporto, colonnina XXS H270 che consente di cucire borse di dimensioni anche molto ridotte ed angoli molto piccoli. Adatta per la cucitura di borse, borse da viaggio, valigette, porta documenti, stivali e calzature in genere. Con la testa 669 il campo di lavoro è stato maggiorato di 75 mm rispetto alla VBO standard, facilitando l'inserimento

di borse molto grandi. La macchina permette la realizzazione di soffiotti e finiture laterali molto vicine al bordo grazie alla placca ago che è stata rialzata e soprattutto alla griffa che consente un trasporto lineare ed assicura una qualità di cucitura sempre perfettamente uniforme. Inoltre, l'innovativo braccio oscillante sincronizzato con la sedia dell'operatore consente il facile inserimento di borse molto grandi o molto piccole.



VBO XXS H270 EVO TRIPLE FEEDING

Machine with oscillating arm, with COMETA hook with needle guard, triple feeding, with XXS post bed H270 which allows to stitch bags of very small dimensions and very small corners. It is suitable for stitching bags, travelling bags, cases, briefcases, boots and footwear in general. With 669 sewing head, the working area has been increased of 75 mm compared to the standard version, facilitating the insertion of very big bags. The machine allows the sewing of side finishes very close to the borders thanks to the needle plate that has been raised and, above all, to the feed dog which enables a constantly linear feeding with the result of a perfectly uniform stitching. In addition, the revolutionary oscillating arm, synchronized with the operator's chair, allows the easy inserting of very small or very big bags.



Altezza colonna 270 mm
Diametro colonna 44 mm
Velocità massima di cucitura 1000 rpm

Post Height 270 mm
Post diameter 44 mm
Sewing maximum speed 1000 rpm

